

Code	Description	Size
------	-------------	------

APARTMENT METERS

SINGLE-JET DRY-DIAL METER FOR COLD AND HOT WATER

Two models available, one with a non-reactive scannable modulator disc (ETKD-M/ETWD-M). The AMK or AMW base models come standard-equipped with a magnet and offer the option of transferring counter data via pulser's.

Performance characteristics in overview

- Single-jet dry dial meter
- Model “-M” with 8-digit register and modulator disc (1 l/pulse) for M-Bus or pulse
- Model “AM” with 7-digit register offers the possibility of remote readout of the meter data via pulser (1 l/pulse)
- Register cap made of high-quality UV-resistant polymer plastic
- Optional: Hermetically sealed glass/copper register IP68 equipped with register cap as a standard
- Register rotatable 355°
- For horizontal and vertical installation (also for ascending and descending pipes)
- Approved in accordance with MID

Applications

- For the measuring cold potable water up to 30 °C (ETKD) or hot water up to 90 °C (ETWD)



COLD APARTMENT METERS

WMZAPT15	15mm	Cold R80 1l/imp (173695 ETKD-N)
WMZAPT20	20mm	Cold R80 1l/imp (173620 ETKD-N)

HOT APARTMENT METERS

WMZAPT15H	15mm	Hot R80 1l/imp (173694 ETWD-N)
WMZAPT20H	20mm	Hot R80 1l/imp (173684 ETWD-N)

PULSE REED SWITCH

WMZMTK-MN		Reed Switch/Pulse for MTKD/APT R80 s (133802)
-----------	--	---

CLIP ON PULSE/M-BUS OUTPUT MODULES FOR MTK AND APARTMENT METERS

WMZMTKCLP-N		EDC-C Pulse Mode U Clip On Reed Switch (140863)
WMZMTKCLP-MB		EDC-C MB Mode Clip On Reed Switch (140823)
WMZMTKCLP-PMB		EDC-C MB + Pulse Mode U Clip On Reed Switch (140869)