

Lead Free Lockable Ball Valve



Brass ball valve featuring a full-port design for high flow, paired with a stainless-steel lever that can be locked in the open or closed position — offering tamper-proof operation and added safety. Ideal for demanding systems where durability, stability, and controlled isolation matter.

Features

Made from lead free DZR CW51L brass, safe use in potable water systems.

Nickel plated brass body

Maximum operating pressure 2500kpa PN25

Working temperature 60°C

WaterMark approved - License No. WM60182



For more information on this product scan the QR code or visit hydroflow.co.nz



Stock Code	Stock Description
HFLBVFF15LF	Ball Valve 15mm F/F Lockable S/S Handle Lead Free
HFLBVFF20LF	Ball Valve 20mm F/F Lockable S/S Handle Lead Free
HFLBVFF25LF	Ball Valve 25mm F/F Lockable S/S Handle Lead Free
HFLBVFF32LF	Ball Valve 32mm F/F Lockable S/S Handle Lead Free
HFLBVFF40LF	Ball Valve 40mm F/F Lockable S/S Handle Lead Free
HFLBVFF50LF	Ball Valve 50mm F/F Lockable S/S Handle Lead Free
HFLBVFF65LF	Ball Valve 65mm F/F Lockable S/S Handle Lead Free

No.	Name	Material
1	Body	CW511L
2	Bonnet	CW511L
3	Ball	SS304
4	Sealing	PTFE
5	Stem	HPb57-3
6	O-ring	EPDM
7	Packing	PTFE
8	Locking cap	HPb57-3
9	Nut	SS304+PVC
11	Handle	SS304+PVC

