

Lead Free Water Ball Valve



Lead free nickel plated DZR brass ball valves are designed to deliver reliable shut-off performance for residential, commercial, and industrial water systems in New Zealand.

Features

Made from high-quality CW511L brass, ensuring excellent strength, corrosion resistance and compliance with New Zealand standards

Equipped with PTFE seats and EPDM o-rings for leak-free performance

Short handle - aluminum
Long handle - 304 stainless steel PVC coated

Maximum operating pressure 2500kpa PN25

Temperature rating 0-80°C

WaterMark approved - License No. WM60182





For more information on this product scan the QR code or visit hydroflow.co.nz





Male Male Short Handle

PRODUCT CODE	PRODUCT DESCRIPTION
HFBVMM15SHLF	Brass Ball Valve M/M 15mm S/H Lead Free
HFBVMM20SHLF	Brass Ball Valve M/M 20mm S/H Lead Free
HFBVMM25SHLF	Brass Ball Valve M/M 25mm S/H Lead Free



Male Male Long Handle

PRODUCT CODE	PRODUCT DESCRIPTION
HFBVMM15LF	Brass Ball Valve M/M 15mm Lead Free
HFBVMM20LF	Brass Ball Valve M/M 20mm Lead Free
HFBVMM25LF	Brass Ball Valve M/M 25mm Lead Free



Male Male Short Handle

DN	PN	A	B	L	L1	L2	H	S
15	25	G1/2"	14.5	60.5	13.5	11.5	42	54
20	25	G3/4"	19	67	14.5	12.5	45	63
25	25	G1"	24.5	80.5	17.5	16	49	72

Male Male Long Handle

DN	PN	A	B	L	L1	L2	H	S
15	25	G1/2"	14.5	60.5	13.5	11.5	49	88
20	25	G3/4"	19	67	14.5	12.5	52	100
25	25	G1"	24.5	80.5	17.5	16	62	125

No.	Description	Material	QTY
10	Handle	Aluminium	1
9	O-ring	EPDM	1
8	Nut	SS304	1
7	Locking cap	HPb57-3	1
6	Packing	PTFE	1
5	Stem	HPb57-3	1
4	Sealing	PTFE	2
3	Ball	SS304	1
2	Bonnet	CW511L	1
1	Body	CW511L	1

No.	Description	Material	QTY
10	Handle	SS304+PVC	1
9	O-ring	EPDM	1
8	Nut	SS304	1
7	Locking cap	HPb57-3	1
6	Packing	PTFE	1
5	Stem	HPb57-3	1
4	Sealing	PTFE	2
3	Ball	SS304	1
2	Bonnet	CW511L	1
1	Body	CW511L	1