

Code	Description	Size	PN Rating
------	-------------	------	-----------

JIM PR1L PURPLE PRIMER

Jim™ PR1L is a hi-etch primer for use on both PVC and CPVC pipe, tubing and socket-type fittings, specifically formulated for all PVC and CPVC pipe applications such as potable water, pressure pipe, gas, conduit, sewers and drain, waste and vent (DWV).

RP4		118ml	
RP8		237ml	
RP946		946ml	



HOT PVC SOLVENT

HOT™ 203I is a polyvinyl chloride (PVC) quick set, solvent cement used for joining PVC pipe and socket type fittings. Blue, medium body cement that is specifically formulated to give an extremely fast drying solvent weld. It is ideal for irrigation, plumbing, pool and spa applications

RH4		118ml	
RH8		237ml	
RH16		473ml	
RH946		946ml	



PETE™ 602 PVC SOLVENT

Pete™ 602L is a polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings. It is a clear, medium body cement. Pete™ 602L is specifically formulated for all PVC pipe applications such as potable water, pressure pipe, gas, conduit, sewers, and drain, waste and vent (DWV).

It is for use on PVC pipe up to and including 6" for Schedule 40 and 1 1/4" for Schedule 80.

RM8		237ml	
RM16		473ml	
RM946		946ml	
RMI		3785ml	



NO. 5 PIPE THREAD SEALANT

RectorSeal® No. 5® is a soft setting, slow drying thread sealant made from special inert fillers dispersed in an oleoresinous base to facilitate its application to threaded pipe connections.

RectorSeal® No. 5® is a unique, versatile and reliable sealant that is non-toxic in accordance with NSF Standard 61. RectorSeal® No. 5® is recommended for pipe made of galvanized steel, iron, brass, copper, aluminium, stainless steel, polyethylene, reinforced fibreglass, and PVC. DO NOT USE ON ABS

R54		118ml	
R58		237ml	
R516		473ml	
R5946		946ml	



Code	Description	Size	PN Rating
------	-------------	------	-----------

RECTORSEAL T PLUS 2 PIPE THREAD SEALANT

RectorSeal® T Plus® is a non-hardening thread sealant containing PTFE plus synthetic fibres. These fibres dispersed in a resinous base combined with inert mineral fillers provide maximum sealing performance. Its low coefficient of friction allows tighter joint makeup with lower torque. It also breaks out easily without galling, seizing, or damaging threads. It is excellent for service where immediate pressurization is necessary. RectorSeal® T Plus 2® is non-toxic in accordance with NSF Standard 61.

RTP4	118ml	1/4pt	
RTP8	237ml	1/2pt	
RTP16	473ml	1pt	
RTP946	946ml	1qt	

*DuPont Registered Trademark



RECTORSEAL ROOT DESTROYER

RectorSeal® Root Destroyer is formulated to destroy and control the growth of roots which enter sewer systems through the pipe joints or cracks. When applied as directed, it is absorbed only by the roots it comes in contact with in the pipes. It attacks and dissolves blockages causing these roots to wither away thus allowing sewage to flow freely through the system. Will not harm tree or shrub roots except where they entered pipes

RRD2		900gm	
------	--	-------	--



PLUMBERS GREASE

Lubricates faucets, stems valves

RPG2		59ml	
------	--	------	--



Code	Description	Size	PN Rating
------	-------------	------	-----------

GO AEROSOL SPRAY WELD

Go Aerosol Spray Weld is a one-step primer/cleaner and solvent weld cement all delivered in a sealed aerosol system. The product is recommended for solvent welding PVC pipe and fittings up to 6" diameter Schedule 40, Schedule 80 & other PVC pipe. Go Aerosol Spray Weld can be used for potable water, sewer and drain, waste and vent systems.

SWCP-100	Purple	11oz	
SWCP-100-6	Purple	4.5oz	
SWCC-100	Clear	11oz	
SWCC-100-6	Clear	4.5oz	



SLIKSTYX

Spray on gasket lubricant
SLIKSTYX

9.75oz



CEELON PTFE THREAD SEAL TAPE

Ceelon tape is made from pure PTFE. A non toxic plastic which is inert to acids, alkalis, solvents, petrol and steam. Self lubricating, will not dry out, harden or crack with age.
Temperature range - 260° - +260°C

Must order in box or carton lots

C/RED	10 x 12 x 0.75mm	Display Box	24 Rolls
C/RED	10 x 12 x 0.75mm	Outer Carton	240 Rolls
C/BLUE	12 x 18 x 0.75mm	Display Box	16 Rolls
C/BLUE	12 x 18 x 0.75mm	Outer Carton	160 Rolls
C/GREEN	12 x 24 x 0.75mm	Display Box	16 Rolls
C/GREEN	12 x 24 x 0.75mm	Outer Carton	60 Rolls



PTFE12	Thread Tape	12mm	Each
--------	-------------	------	------



DH	Dressed Hemp (thread sealant)	80gm	Each
V-Hemp	Plumber Hemp	500gm	45 metres



Code	Description	Size	PN Rating
------	-------------	------	-----------

PETROLATUM TAPE ST

UCC Petrolatum Tape is composed of a non woven synthetic fabric carrier fully impregnated with neutral petrolatum compound, stabilised with inert fillers and complemented with corrosion inhibitors

UCC Petrolatum Tape is designed to provide long term corrosion protection to pipes, flanges, valves, and other fittings.

UPT-50ST		50mm x 10mtr	
UPT-75ST		75mm x 10mtr	
UPT-100ST		100mm x 10mtr	
UPT-150ST		150mm x 10mtr	

